

## KILNS FOR CERAMICS

### ELECTRIC HOBBY KILNS - FRONT LOADERS

kiln model	operational temperature	inner volume (l)	inner dimensions (mm)			outer dimensions (mm)			heating power	voltage	price
			width	length	height	width	length	height			
KH 30-12,8	1280 °C	36	300	360	330	640	885	800	3 kW	1 x 230 V	3 810 €
KH 60-12,8	1280 °C	70	380	420	440	730	950	1570	5,2 kW	3 x 400 V	5 830 €
KH 125-12,8	1280 °C	144	470	520	590	820	1060	1580	9 kW	3 x 400 V	7 730 €
KH 180-12,8	1280 °C	194	530	590	620	880	1120	1680	12 kW	3 x 400 V	8 000 €

### ELECTRIC CHAMBER KILNS FOR PROFESSIONAL FIRING

kiln model	operational temperature	inner volume (l)	inner dimensions (mm)			outer dimensions (mm)			heating power	voltage	price
			width	length	height	width	length	height			
KY 180-12,8	1280 °C	194	550	550	640	920	1140	1680	12 kW	3 x 400 V	9 140 €
KY 250-12,8	1280 °C	269	680	550	720	1060	1160	1680	14 kW	3 x 400 V	10 350 €
KY 300-12,8	1280 °C	318	680	650	720	1060	1240	1680	17 kW	3 x 400 V	11 190 €
KY 400-12,8	1280 °C	411	780	650	810	1160	1240	1800	24 kW	3 x 400 V	14 750 €
KY 500-12,8	1280 °C	551	810	820	830	1250	1510	1865	28 kW	3 x 400 V	16 950 €
KY 650-12,8	1280 °C	680	880	750	1030	1300	1370	1980	30 kW	3 x 400 V	18 560 €
KY 850-12,8	1280 °C	859	880	820	1190	1300	1440	1980	37 kW	3 x 400 V	22 130 €
KY 1150-12,8	1280 °C	1152	1080	860	1240	1550	1650	2020	44 kW	3 x 400 V	24 930 €
KY 1350-12,8	1280 °C	1337	1080	960	1290	1600	1900	2070	52 kW	3 x 400 V	<i>upon request</i>
KY 1650-12,8	1280 °C	1647	1330	960	1290	1850	1900	2070	64 kW	3 x 400 V	<i>upon request</i>
KY 1850-12,8	1280 °C	1836	1330	1070	1290	1850	2010	2070	72 kW	3 x 400 V	<i>upon request</i>
KY 2200-12,8	1280 °C	2179	1330	1270	1290	1850	2210	2070	85 kW	3 x 400 V	<i>upon request</i>
KY 180-13,3	1330 °C	154	500	540	570	920	1140	1680	12 kW	3 x 400 V	11 780 €
KY 250-13,3	1330 °C	196	600	510	640	1060	1160	1680	14 kW	3 x 400 V	13 200 €
KY 300-13,3	1330 °C	234	600	610	640	1060	1240	1680	17 kW	3 x 400 V	14 380 €
KY 400-13,3	1330 °C	312	700	610	730	1160	1240	1800	24 kW	3 x 400 V	16 880 €
KY 500-13,3	1330 °C	427	730	780	750	1250	1510	1865	28 kW	3 x 400 V	22 030 €
KY 650-13,3	1330 °C	540	800	710	950	1300	1370	1980	30 kW	3 x 400 V	24 550 €
KY 850-13,3	1330 °C	657	800	740	1110	1300	1440	1980	37 kW	3 x 400 V	29 400 €
KY 1150-13,3	1330 °C	951	1000	820	1160	1550	1650	2020	44 kW	3 x 400 V	34 430 €
KY 1350-13,3	1330 °C	1113	1000	920	1210	1600	1900	2070	52 kW	3 x 400 V	<i>upon request</i>
KY 1650-13,3	1330 °C	1392	1250	920	1210	1850	1900	2070	64 kW	3 x 400 V	<i>upon request</i>
KY 1850-13,3	1330 °C	1558	1250	1030	1210	1850	2010	2070	72 kW	3 x 400 V	<i>upon request</i>
KY 2200-13,3	1330 °C	1860	1250	1230	1210	1850	2210	2070	85 kW	3 x 400 V	<i>upon request</i>

**NB: Price includes** complete kiln in standard version incl. a controller and a shelf to cover the kiln bottom, technical documentation, operating instructions, CE certificate.

**Price excludes** VAT of country of destination, transport, packaging and setting into operation.